

**Walttools**1262 Leah Rd  
Morris, IL 60450DATE ISSUED 4/14/2003 24 HOUR EMERGENCY PHONE  
DATE REVISED 12/13/2006 800-535-5053

888 263 5895

**MATERIAL SAFETY DATA SHEET****SECTION I / IDENTIFICATION OF MATERIAL**

<b>PRODUCT NAME</b>	30 VOC 100 California		
<b>USE</b>	Concrete coating	<b>CHEMICAL FAMILY</b>	ACRYLIC SOLUTION

**SECTION II / HAZARDOUS INGREDIENTS**

COMPONENT	CAS #	%	TVL(ACGIH)	PEL(OSHA)
Acetone	67-64-1	40-50	N/A	N/A
Benzene, 1 - chloro-4-(trifluoromethyl)	98-56-6	20-30	100 ppm	100 ppm

**SECTION III / PHYSICAL DATA**

<b>APPEARANCE &amp; ODOR</b>	CLEAR LIQUID WITH SOLVENT ODOR		
<b>MELTING POINT (°C)</b>	N/A	<b>BOILING POINT (°C)</b>	300 deg F
<b>DENSITY (g/ml)</b>	N/A	<b>SPECIFIC GRAVITY</b>	.92
<b>% WATER</b>	0	<b>VOC grams/liter</b>	100
<b>VAPOR PRESSURE (mm Hg)</b>	N/A	<b>VISCOSITY</b>	N/A
<b>SOLUBILITY IN WATER</b>	NEGATIVE	<b>PH</b>	N/A

**SECTION IV / FIRE AND EXPLOSION HAZARD DATA**

<b>FLASHPOINT</b>	<20° F	<b>METHOD</b>	TCC/PM	<b>FLAMMABLE LIMITS</b>	LEL	1.00	UEL	7.00
<b>EXTINGUISHING MEDIA</b>	DRY FILM ONLY. DRY CHEMICAL, Co2, WATER FOG.							
<b>SPECIAL FIREFIGHTING PROCEDURES</b>	WEAR SELF-CONTAINING BREATHING APPARATUS.							
<b>UNUSUAL FIRE AND EXPLOSION HAZARDS</b>	KEEP CONTAINERS ISOLATED FROM HEAT AND TIGHTLY CLOSED							

**SECTION V / REACTIVITY DATA**

<b>STABILITY (CHECK ONE)</b>	UNSTABLE		STABLE	X
<b>CONDITIONS TO AVOID</b>	N/A			
<b>INCOMPATIBILITY</b>	N/A			
<b>HAZARDOUS DECOMPOSITION PRODUCTS</b>	NO			

### SECTION VI / HEALTH HAZARD DATA

<b>EFFECTS OF EXPOSURE</b>	<b>DERMAL</b>	Irritation and cracking of skin in severe cases. Clean with soap and water. Seek medical attention if symptoms persist.							
	<b>EYE</b>	Will cause irritation. Flush with water for 15 minutes. Seek medical attention if problem persists.							
	<b>INHALATION</b>	May cause dizziness and light headiness. Remove to fresh air.							
	<b>INGESTION</b>	Seek medical attention. <b>DO NOT INDUCE VOMITING!</b>							
<b>EMERGENCY FIRST AID</b>	<b>DERMAL</b>	IMMEDIATELY FLUSH WITH WATER AND REMOVE SOILED CLOTHING							
	<b>EYE</b>	IMMEDIATELY FLUSH WITH WATER FOR AT LEAST 15 MINUTES							
	<b>INHALATION</b>	REMOVE TO FRESH AIR. SEEK MEDICAL ATTENTION IF NECESSARY.							
	<b>INGESTION</b>	SEEK MEDICAL ATTENTION IMMEDIATELY							
<b>CARCINOGENICITY</b>	<b>IARC</b>	NO		<b>OSHA</b>	NO		<b>NTP</b>	NO	
<b>TOXICITY</b>	<b>EYE</b>	N/A	<b>ORAL</b>	N/A	<b>INHALATION</b>	N/A	<b>DERMAL</b>	N/A	
<b>OTHER</b>									

### SECTION VII / SPILL PROCEDURES AND HANDLING REQUIREMENTS

<b>SPILL AND LEAK PROCEDURES</b>	WEAR PROTECTIVE CLOTHING. STOP LEAK, AND CONTAIN SPILL.	
<b>WASTE DISPOSAL PROCEDURES</b>	DISPOSE OF IN ACCORDANCE WITH APPLICABLE LOCAL, STATE, AND FEDERAL REGULATIONS.	
<b>HANDLING AND STORAGE PRECAUTIONS</b>	HANDLE WITH ACCEPTED PRACTICES FOR LIQUID DRUMS.	
<b>SPECIAL PRECAUTIONS</b>	N/A	

### SECTION VII / SPECIAL PROTECTION INFORMATION

<b>RESPIRATORY</b>	USE NIOSH OR MSHA APPROVED CARTRIDGE RESPIRATOR.
<b>SKIN</b>	NITRILE RUBBER GLOVES RECOMMENDED
<b>EYE</b>	SAFETY GLASSES RECOMMENDED
<b>VENTILLATION</b>	LOCAL EXHAUST RECOMMENDED
<b>OTHER</b>	CLEAN , LONG LEGGED. LONG SLEEVED CLOTHING

### SECTION IX / TRANSPORTATION INFORMATION

<b>TSCA STATUS</b>	N/A		<b>DOT SHIPPING INFORMATION</b>	PAINT RELATED MATERIAL,3, UN 1263, PG II	
<b>HMIS/NFP RATINGS</b>	<b>HEALTH</b>	2	<b>FLAMMABILITY</b>	3	<b>REACTIVITY</b> 0
<b>OTHER</b>					

N/A = NOT APPLICABLE      N/D = NOT DETECTED

THIS DOCUMENT HAS BEEN PREPARED USING DATA FROM SOURCES CONSIDERED TECHNICALLY RELIABLE. THERE ARE NO GUARANTEES TO ITS ACCURACY OR SUITABILITY TO SPECIFIC APPLICATIONS. ACTUAL CONDITIONS OF USE, HANDLING, AND END PRODUCT PERFORMANCE ARE THE SOLE RESPONSIBILITY OF THE USER. THE USER ASSUMES ALL RISK AND LIABILITY FOR USE , INCLUDING COMPLIANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.