

**Walttools**  
1246 Leah rd  
Morris, IL 60450  
888.263.5895

DATE ISSUED 05/23/2016  
DATE REVISED 05/23/2016

24 HOUR EMERGENCY PHONE  
800-535-5053

## MATERIAL SAFETY DATA SHEET

### SECTION I / IDENTIFICATION OF MATERIAL

<b>PRODUCT NAME</b>	True Impressions Cure Seal 700		
<b>USE</b>	Concrete coating	<b>CHEMICAL FAMILY</b>	ACRYLIC SOLUTION

### SECTION II / HAZARDOUS INGREDIENTS

COMPONENT	CAS #	%	TVL(ACGIH)	PEL(OSHA)
Xylene	1330-30-7	<50	200 ppm	100 ppm
Dimethyl Carbonate	616-38-6		N/A	N/A

### SECTION III / PHYSICAL DATA

<b>APPEARANCE &amp; ODOR</b>	CLEAR LIQUID WITH SOLVENT ODOR		
<b>MELTING POINT ( C )</b>	N/A	<b>BOILING POINT ( F )</b>	201 deg F
<b>DENSITY (g/ml)</b>	N/A	<b>SPECIFIC GRAVITY</b>	. 899
<b>% WATER</b>	0	<b>VOC grams/liter</b>	< 350
<b>VAPOR PRESSURE (mm Hg)</b>	N/A	<b>VISCOSITY</b>	N/A
<b>SOLUBILITY IN WATER</b>	NEGATIVE	<b>PH</b>	N/A

### SECTION IV / FIRE AND EXPLOSION HAZARD DATA

<b>FLASHPOINT</b>	39.92 F	<b>METHOD</b>	TCC/PM	<b>FLAMMABLE LIMITS</b>	LEL	1. 00	UEL	7. 00
<b>EXTINGUISHING MEDIA</b>	DRY FILM ONLY. DRY CHEMICAL, Co2, WATER FOG.							
<b>SPECIAL FIREFIGHTING PROCEDURES</b>	WEAR SELF-CONTAINING BREATHING APPARATUS.							
<b>UNUSUAL FIRE AND EXPLOSION HAZARDS</b>	KEEP CONTAINERS ISOLATED FROM HEAT AND TIGHTLY CLOSED							

### SECTION V / REACTIVITY DATA

<b>STABILITY (CHECK ONE)</b>	UNSTABLE		STABLE	X
<b>CONDITIONS TO AVOID</b>	Extreme Heat, Sparks, Flame, (gas heaters, pilot lights)			
<b>INCOMPATIBILITY</b>	N/A			
<b>HAZARDOUS DECOMPOSITION PRODUCTS</b>	NO			

### SECTION VI / HEALTH HAZARD DATA

<b>EFFECTS OF EXPOSURE</b>	<b>DERMAL</b>	Irritation and cracking of skin in severe cases. Clean with soap and water. Seek medical attention if symptoms persist.						
	<b>EYE</b>	Will cause irritation. Flush with water for 15 minutes. Seek medical attention if problem persists.						
	<b>INHALATION</b>	May cause dizziness and light headiness. Remove to fresh air.						
	<b>INGESTION</b>	Seek medical attention. DO NOT INDUCE VOMITING!						
<b>EMERGENCY FIRST AID</b>	<b>DERMAL</b>	IMMEDIATELY FLUSH WITH WATER AND REMOVE SOILED CLOTHING						
	<b>EYE</b>	IMMEDIATELY FLUSH WITH WATER FOR AT LEAST 15 MINUTES						
	<b>INHALATION</b>	REMOVE TO FRESH AIR. SEEK MEDICAL ATTENTION IF NECESSARY.						
	<b>INGESTION</b>	SEEK MEDICAL ATTENTION IMMEDIATELY						
<b>CARCINOGENICITY</b>	<b>IARC</b>	NO	<b>OSHA</b>	NO	<b>NTP</b>	NO		
<b>TOXICITY</b>	<b>EYE</b>	N/A	<b>ORAL</b>	N/A	<b>INHALATION</b>	N/A	<b>DERMAL</b>	N/A
<b>OTHER</b>								

### SECTION VII / SPILL PROCEDURES AND HANDLING REQUIREMENTS

<b>SPILL AND LEAK PROCEDURES</b>	WEAR PROTECTIVE CLOTHING. STOP LEAK, AND CONTAIN SPILL.
<b>WASTE DISPOSAL PROCEDURES</b>	DISPOSE OF IN ACCORDANCE WITH APPLICABLE LOCAL, STATE, AND FEDERAL REGULATIONS.
<b>HANDLING AND STORAGE PRECAUTIONS</b>	HANDLE WITH ACCEPTED PRACTICES FOR LIQUID DRUMS.
<b>SPECIAL PRECAUTIONS</b>	N/A

### SECTION VII / SPECIAL PROTECTION INFORMATION

<b>RESPIRATORY</b>	USE NIOSH OR MSHA APPROVED CARTRIDGE RESPIRATOR.
<b>SKIN</b>	NITRILE RUBBER GLOVES RECOMMENDED
<b>EYE</b>	SAFETY GLASSES RECOMMENDED
<b>VENTILLATION</b>	LOCAL EXHAUST RECOMMENDED
<b>OTHER</b>	CLEAN , LONG LEGGED. LONG SLEEVED CLOTHING

### SECTION IX / TRANSPORTATION INFORMATION

<b>TSCA STATUS</b>	N/A	<b>DOT SHIPPING INFORMATION</b>	PAINT RELATED MATERIAL, 3, UN1263, PGII			
<b>HMIS/NFP RATINGS</b>	<b>HEALTH</b>	1	<b>FLAMMABILITY</b>	3	<b>REACTIVITY</b>	0
<b>OTHER</b>						

N/A = NOT APPLICABLE      N/D = NOT DETECTED

THIS DOCUMENT HAS BEEN PREPARED USING DATA FROM SOURCES CONSIDERED TECHNICALLY RELIABLE. THERE ARE NO GUARANTEES TO ITS ACCURACY OR SUITABILITY TO SPECIFIC APPLICATIONS. ACTUAL CONDITIONS OF USE, HANDLING, AND END PRODUCT PERFORMANCE ARE THE SOLE RESPONSIBILITY OF THE USER. THE USER ASSUMES ALL RISK AND LIABILITY FOR USE BEYOND WALTTOOLS/CONTRACTOR SOURCE. CONTROL , INCLUDING COMPLIANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.