

SAFETY DATA SHEET

Product name: Waltools WP-50

Issue Date: 10/01/2019

1. IDENTIFICATION

Product name: Waltools WP-50

Recommended use of the chemical and restrictions on use

Identified uses: Impregnation agents Process regulators, other than polymerization or vulcanization processes

COMPANY IDENTIFICATION

Waltools 1246 Leah Rd Morris, IL 60450

Customer Information Number:

888-263-5895
cs@waltools.com

EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact: INFOTREC +1 800-535-5053

Local Emergency Contact: 815-941-4215

2. HAZARDS IDENTIFICATION

Hazard classification

GHS classification in accordance with 29 CFR 1910.1200

Skin irritation - Category 2

Label elements

Hazard pictograms



Signal word: **WARNING!**

Hazards

Causes skin irritation.

Precautionary statements**Prevention**

Wash skin thoroughly after handling.
Wear protective gloves.

Response

IF ON SKIN: Wash with plenty of soap and water.
If skin irritation occurs: Get medical advice/ attention.
Take off contaminated clothing and wash before reuse.

Other hazards

No data available

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature: Silicone compound

This product is a mixture.

Component	CASRN	Concentration
Sodium aluminum silicate	1344-00-9	>= 52.0 - <= 73.0 %
Triethoxy(octyl)silane	2943-75-1	>= 6.0 - <= 15.0 %
Methanol	67-56-1	>= 0.1 - <= 0.15 %

4. FIRST AID MEASURES**Description of first aid measures****General advice:**

If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation: Move person to fresh air; if effects occur, consult a physician.

Skin contact: Wash off with plenty of water. Suitable emergency safety shower facility should be available in work area.

Eye contact: Flush eyes with plenty of water; remove contact lenses after the first 1-2 minutes then continue flushing for several minutes. Only mechanical effects expected. If effects occur, consult a physician, preferably an ophthalmologist.

Ingestion: No emergency medical treatment necessary.

Most important symptoms and effects, both acute and delayed:

Product name: Walttool WP-50

Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

Indication of any immediate medical attention and special treatment needed

Notes to physician: No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

5. FIREFIGHTING MEASURES

Extinguishing media

Suitable extinguishing media: Water spray. Alcohol-resistant foam. Carbon dioxide (CO₂). Dry chemical.

Unsuitable extinguishing media: None known..

Special hazards arising from the substance or mixture

Hazardous combustion products: Oxides of phosphorus. Carbon oxides. Silicon oxides.

Unusual Fire and Explosion Hazards: Exposure to combustion products may be a hazard to health..

Advice for firefighters

Fire Fighting Procedures: Collect contaminated fire extinguishing water separately. This must not be discharged into drains.. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.. Contain fire water run-off if possible. Fire water run-off, if not contained, may cause environmental damage.. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.

Special protective equipment for firefighters: In the event of fire, wear self-contained breathing apparatus.. Use personal protective equipment..

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Use personal protective equipment. Follow safe handling advice and personal protective equipment recommendations.

Environmental precautions: Do not release the product to the aquatic environment above defined regulatory levels. Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up: Sweep up or vacuum up spillage and collect in suitable container for disposal. Avoid dispersal of dust in the air (i.e., clearing dust surfaces

Product name: Waltools WP-50

with compressed air). Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

See sections: 7, 8, 11, 12 and 13.

7. HANDLING AND STORAGE

Precautions for safe handling: Do not get on skin or clothing. Do not breathe dust. Do not swallow. Avoid contact with eyes. Keep container closed when not in use. Take care to prevent spills, waste and minimize release to the environment. Handle in accordance with good industrial hygiene and safety practice.

Use only with adequate ventilation. See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Conditions for safe storage: Keep in properly labelled containers. Store in accordance with the particular national regulations.

Do not store with the following product types: Strong oxidizing agents.
Unsuitable materials for containers: None known.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Control parameters**

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

Component	Regulation	Type of listing	Value
Sodium aluminum silicate	ACGIH	TWA Respirable fraction	1 mg/m3 , Aluminium
	Further information: LRT irr: Lower Respiratory Tract irritation; pneumoconiosis: Pneumoconiosis; neurotoxicity: Neurotoxicity; A4: Not classifiable as a human carcinogen; varies: varies		
Methanol	ACGIH	TWA	200 ppm
	Further information: headache: Headache; nausea: Nausea; dizziness: Dizziness; eye dam: Eye damage; BEI: Substances for which there is a Biological Exposure Index or Indices (see BEI® section); Skin: Danger of cutaneous absorption		
	ACGIH	STEL	250 ppm
	Further information: headache: Headache; nausea: Nausea; dizziness: Dizziness; eye dam: Eye damage; BEI: Substances for which there is a Biological Exposure Index or Indices (see BEI® section); Skin: Danger of cutaneous absorption		
	OSHA Z-1	TWA	260 mg/m3 200 ppm
	Further information: (b): The value in mg/m3 is approximate.		
	OSHA P0	STEL	325 mg/m3 250 ppm
	Further information: X: Skin notation		
	OSHA P0	TWA	260 mg/m3 200 ppm
	Further information: X: Skin notation		
Ethanol	ACGIH	TWA	1,000 ppm
	Further information: URT irr: Upper Respiratory Tract irritation		
	ACGIH	STEL	1,000 ppm
	Further information: URT irr: Upper Respiratory Tract irritation		
	OSHA Z-1	TWA	1,900 mg/m3 1,000 ppm

Further information: (b): The value in mg/m3 is approximate.			
	CAL PEL	PEL	1,900 mg/m3 1,000 ppm
	OSHA P0	TWA	1,900 mg/m3 1,000 ppm

The following substance(s), which have Occupational Exposure Limit(s) (OEL), may be formed during handling or processing:
Ethanol

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Methanol	67-56-1	Methanol	Urine	End of shift (As soon as possible after exposure ceases)	15 mg/l	ACGIH BEI

Exposure controls

Engineering controls: Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some operations.

Individual protection measures

Eye/face protection: Use safety glasses (with side shields). If there is a potential for exposure to particles which could cause eye discomfort, wear chemical goggles.

Skin protection

Hand protection: Use gloves chemically resistant to this material. Examples of preferred glove barrier materials include: Polyvinyl chloride ("PVC" or "vinyl"). Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). **NOTICE:** The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Other protection: Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task.

Respiratory protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. In dusty or misty atmospheres, use an approved particulate respirator. The following should be effective types of air-purifying respirators: Organic vapor cartridge with a particulate pre-filter.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	
Physical state	coarse powder
Color	off-white
Odor	slight
Odor Threshold	No data available
pH	Not applicable
Melting point/range	No data available
Freezing point	No data available
Boiling point (760 mmHg)	Not applicable
Flash point	closed cup >100 °C (212 °F)
Evaporation Rate (Butyl Acetate = 1)	Not applicable
Flammability (solid, gas)	Not classified as a flammability hazard
Lower explosion limit	No data available
Upper explosion limit	No data available
Vapor Pressure	Not applicable
Relative Vapor Density (air = 1)	No data available
Relative Density (water = 1)	0.61
Water solubility	No data available
Partition coefficient: n-octanol/water	No data available
Auto-ignition temperature	No data available
Decomposition temperature	No data available
Dynamic Viscosity	Not applicable
Kinematic Viscosity	Not applicable
Explosive properties	Not explosive
Oxidizing properties	The substance or mixture is not classified as oxidizing.
Molecular weight	No data available
Particle size	No data available

NOTE: The physical data presented above are typical values and should not be construed as a specification.

10. STABILITY AND REACTIVITY

Reactivity: Not classified as a reactivity hazard.

Chemical stability: Stable under normal conditions.

Possibility of hazardous reactions: Can react with strong oxidizing agents. When heated to temperatures above 150 °C (300 °F) in the presence of air, product can form formaldehyde vapours.

Safe handling conditions may be maintained by keeping vapour concentrations within the occupational exposure limit for formaldehyde.

Conditions to avoid: None known.

Incompatible materials: Oxidizing agents

Hazardous decomposition products:

Decomposition products can include and are not limited to: Formaldehyde. Ethanol. Acrolein. Acetic acid.

11. TOXICOLOGICAL INFORMATION

Toxicological information appears in this section when such data is available.

Information on likely routes of exposure

Inhalation, Eye contact, Skin contact, Ingestion.

Acute toxicity (represents short term exposures with immediate effects - no chronic/delayed effects known unless otherwise noted)

Acute oral toxicity

Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts.

As product: Single dose oral LD50 has not been determined.

Based on information for component(s):

LD50, Rat, > 5,000 mg/kg Estimated.

Information for components:

Sodium aluminum silicate

LD50, Rat, > 5,000 mg/kg

LD50, Rat, male and female, > 10,000 mg/kg

Triethoxy(octyl)silane

Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts.

LD50, Rat, male and female, 5,110 mg/kg OECD 401 or equivalent

Methanol

Methanol is highly toxic to humans and may cause central nervous system effects, visual disturbances up to blindness, metabolic acidosis, and degenerative damage to other organs including liver, kidney, and heart. Effects may be delayed. LD50, Rat, > 5,000 mg/kg

Lethal Dose, Humans, 340 mg/kg Estimated.

Lethal Dose, Humans, 29 - 237 ml Estimated.

Acute dermal toxicity

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

As product: The dermal LD50 has not been determined.

Based on information for component(s):
LD50, Rabbit, > 2,000 mg/kg Estimated.

Information for components:

Sodium aluminum silicate

LD50, Rabbit, > 2,000 mg/kg No deaths occurred at this concentration.

LD50, Rabbit, > 5,000 mg/kg

Triethoxy(octyl)silane

LD50, Rabbit, female, 8,000 mg/kg OECD 402 or equivalent

LD50, Rabbit, male, 6,730 mg/kg OECD 402 or equivalent

Methanol

Effects of methanol are the same as observed via oral and inhalation exposure and include central nervous system (CNS) depression, visual impairment up to blindness, metabolic acidosis, with effects on organ systems such as liver, kidneys and heart, even death. LD50, Rabbit, 15,800 mg/kg

Acute inhalation toxicity

At room temperature, exposure to vapor is minimal due to low volatility; single exposure is not likely to be hazardous. Dust may cause irritation to upper respiratory tract (nose and throat).

As product: The LC50 has not been determined.

Information for components:

Sodium aluminum silicate

Dust may cause irritation to upper respiratory tract (nose and throat).

LC50, Rat, 1 Hour, Aerosol, > 18.3 mg/l

LC50, Rat, male and female, 4 Hour, dust/mist, > 58.8 mg/l

Triethoxy(octyl)silane

LC50, Rat, male and female, 4 hrs, vapour, > 22 ppm OECD Test Guideline 403 No deaths occurred at this concentration.

Methanol

Easily attainable vapor concentrations may cause serious adverse effects, even death. At lower concentrations: May cause respiratory irritation and central nervous system depression. Symptoms may include headache, dizziness and drowsiness, progressing to incoordination and unconsciousness. Inhalation of methanol may cause effects ranging from headache, narcosis and visual impairment to metabolic acidosis, blindness, and even death. Effects may be delayed.

LC50, Rat, 4 Hour, vapour, 3 mg/l

Skin corrosion/irritation

Based on information for component(s):

Brief contact may cause moderate skin irritation with local redness.

Prolonged contact may cause moderate skin irritation with local redness.

Information for components:

Sodium aluminum silicate

Prolonged exposure not likely to cause significant skin irritation.

Triethoxy(octyl)silane

Brief contact may cause moderate skin irritation with local redness.

Prolonged contact may cause moderate skin irritation with local redness.

Methanol

Prolonged contact may cause slight skin irritation with local redness.

Serious eye damage/eye irritation

Based on information for component(s):

Solid or dust may cause irritation or corneal injury due to mechanical action.

Information for components:

Sodium aluminum silicate

May cause slight temporary eye irritation.

Triethoxy(octyl)silane

May cause slight eye irritation.

Corneal injury is unlikely.

Methanol

May cause eye irritation.

Sensitization

For skin sensitization:

Did not cause allergic skin reactions when tested in humans.

Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

Information for components:

Sodium aluminum silicate

Did not cause allergic skin reactions when tested in humans.

Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

Triethoxy(octyl)silane

For similar material(s):
Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:
No relevant data found.

Methanol

For skin sensitization:
No relevant data found.

For respiratory sensitization:
No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure)

Contains component(s) which are classified as specific target organ toxicant, single exposure, category 1.

Information for components:

Sodium aluminum silicate

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Triethoxy(octyl)silane

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Methanol

Causes damage to organs.
Route of Exposure: Oral
Target Organs: Eyes, Central nervous system

Aspiration Hazard

Based on physical properties, not likely to be an aspiration hazard.

Information for components:

Sodium aluminum silicate

Based on physical properties, not likely to be an aspiration hazard.

Triethoxy(octyl)silane

May be harmful if swallowed and enters airways.

Methanol

May be harmful if swallowed and enters airways.

Chronic toxicity (represents longer term exposures with repeated dose resulting in chronic/delayed effects - no immediate effects known unless otherwise noted)

Specific Target Organ Systemic Toxicity (Repeated Exposure)

Based on information for component(s):
In animals, effects have been reported on the following organs:
Urinary tract.

Information for components:

Sodium aluminum silicate

Based on available data, repeated exposures are not anticipated to cause additional significant adverse effects.

Triethoxy(octyl)silane

In animals, effects have been reported on the following organs:

Urinary tract.

Findings from a combined repeated-dose toxicity study with reproductive/developmental screening endpoints on n-octyltriethoxysilane have shown neurological effects in rats at high doses (1000 mg/kg). Paralysis and paresis of the limbs, and demyelination of the brain, spinal cord, sciatic and tibial nerves was noted in some animals.

Methanol

Methanol is highly toxic to humans and may cause central nervous system effects, visual disturbances up to blindness, metabolic acidosis, and degenerative damage to other organs including liver, kidney, and heart.

Carcinogenicity

Based on information for component(s): Did not cause cancer in laboratory animals.

Information for components:

Sodium aluminum silicate

Did not cause cancer in laboratory animals.

Triethoxy(octyl)silane

No relevant data found.

Methanol

Did not cause cancer in laboratory animals.

Teratogenicity

Based on information for component(s): Did not cause birth defects or any other fetal effects in laboratory animals.

Information for components:

Sodium aluminum silicate

Did not cause birth defects or any other fetal effects in laboratory animals.

Triethoxy(octyl)silane

Did not cause birth defects or any other fetal effects in laboratory animals.

Methanol

Methanol has caused birth defects in mice at doses nontoxic to the mother as well as slight behavioral effects in offspring of rats.

Reproductive toxicity

No relevant data found.

Information for components:

Sodium aluminum silicate

No relevant data found.

Triethoxy(octyl)silane

In animal studies, did not interfere with reproduction.

Methanol

In animal studies, did not interfere with reproduction.

Mutagenicity

Based on information for component(s): In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

Information for components:

Sodium aluminum silicate

In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

Triethoxy(octyl)silane

In vitro genetic toxicity studies were negative.

Methanol

In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative in some cases and positive in other cases.

12. ECOLOGICAL INFORMATION

Ecotoxicological information appears in this section when such data is available.

Toxicity

Sodium aluminum silicate

Acute toxicity to fish

Material is practically non-toxic to fish on an acute basis (LC50 > 100 mg/L).
LC50, Danio rerio (zebra fish), semi-static test, 96 Hour, > 1,800 mg/l, OECD Test Guideline 203 or Equivalent

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), 48 Hour, 1,000 - 1,800 mg/l

Acute toxicity to algae/aquatic plants

EbC50, Algae, 96 Hour, Biomass, 180 - 320 mg/l

Triethoxy(octyl)silane

Acute toxicity to fish

Not expected to be acutely toxic to aquatic organisms.
No toxicity at the limit of solubility
LC50, Oncorhynchus mykiss (rainbow trout), flow-through, 96 hrs, > 0.055 mg/l, OECD Test Guideline 203 or Equivalent

Acute toxicity to aquatic invertebrates

Product name: Waltools WP-50

No toxicity at the limit of solubility
EC50, Daphnia magna (Water flea), flow-through test, 48 hrs, > 0.049 mg/l, OECD Test Guideline 202 or Equivalent

Acute toxicity to algae/aquatic plants

No toxicity at the limit of solubility
ErC50, Pseudokirchneriella subcapitata (green algae), static test, 72 hrs, Growth rate inhibition, > 0.13 mg/l, OECD Test Guideline 201 or Equivalent
No toxicity at the limit of solubility
NOEC, Pseudokirchneriella subcapitata (green algae), static test, 72 hrs, Growth rate inhibition, > 0.13 mg/l, OECD Test Guideline 201 or Equivalent

Chronic toxicity to aquatic invertebrates

NOEC, Daphnia magna (Water flea), 21 d, number of offspring, 0.199 mg/l

Methanol**Acute toxicity to fish**

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).
LC50, Bluegill sunfish (Lepomis macrochirus), flow-through test, 96 Hour, 15,400 mg/l

Acute toxicity to aquatic invertebrates

LC50, Daphnia magna (Water flea), 48 Hour, > 10,000 mg/l

Acute toxicity to algae/aquatic plants

ErC50, Pseudokirchneriella subcapitata (green algae), 96 Hour, Growth rate, 22,000 mg/l, OECD Test Guideline 201 or Equivalent

Toxicity to bacteria

IC50, activated sludge, 3 Hour, Respiration rates., > 1,000 mg/l, OECD Test Guideline 209

Chronic toxicity to fish

NOEC, Oryzias latipes (Orange-red killifish), 200 Hour, 15,800 mg/l

Persistence and degradability**Sodium aluminum silicate**

Biodegradability: Biodegradation is not applicable.

Triethoxy(octyl)silane

Biodegradability: Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable; however, these results do not necessarily mean that the material is not biodegradable under environmental conditions.

10-day Window: Fail

Biodegradation: 31.5 %

Exposure time: 28 d

Method: OECD Test Guideline 301D or Equivalent

Methanol

Biodegradability: Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

Theoretical Oxygen Demand: 1.50 mg/mg

Chemical Oxygen Demand: 1.49 mg/mg Dichromate

Biological oxygen demand (BOD)

Incubation Time	BOD
5 d	72 %
20 d	79 %

Photodegradation

Test Type: Half-life (indirect photolysis)

Sensitization: OH radicals

Atmospheric half-life: 8 - 18 d

Method: Estimated.

Bioaccumulative potential

Sodium aluminum silicate

Bioaccumulation: Partitioning from water to n-octanol is not applicable.

Triethoxy(octyl)silane

Bioaccumulation: Bioconcentration potential is high (BCF > 3000 or Log Pow between 5 and 7).

Partition coefficient: n-octanol/water(log Pow): 6.41

Methanol

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Partition coefficient: n-octanol/water(log Pow): -0.77 Measured

Bioconcentration factor (BCF): < 10 *Leuciscus idus* (Golden orfe) Measured

Mobility in soil

Sodium aluminum silicate

No relevant data found.

Triethoxy(octyl)silane

Expected to be relatively immobile in soil (Koc > 5000).

Partition coefficient (Koc): > 5000 Estimated.

Methanol

Potential for mobility in soil is very high (Koc between 0 and 50).

Partition coefficient (Koc): 0.44 Estimated.

13. DISPOSAL CONSIDERATIONS

Disposal methods: DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR

SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Incinerator or other thermal destruction device. For additional information, refer to: Handling & Storage Information, MSDS Section 7 Stability & Reactivity Information, MSDS Section 10 Regulatory Information, MSDS Section 15

Treatment and disposal methods of used packaging: Empty containers should be recycled or otherwise disposed of by an approved waste management facility. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. Do not re-use containers for any purpose.

14. TRANSPORT INFORMATION

DOT

Not regulated for transport

Classification for SEA transport (IMO-IMDG):

**Transport in bulk
according to Annex I or II
of MARPOL 73/78 and the
IBC or IGC Code**

Not regulated for transport
Consult IMO regulations before transporting ocean bulk

Classification for AIR transport (IATA/ICAO):

Not regulated for transport

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

15. REGULATORY INFORMATION

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

Skin corrosion or irritation

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (CERCLA) Section 103

Calculated RQ exceeds reasonably attainable upper limit.

Components	CASRN	RQ (RCRA Code)
Methanol	67-56-1	5000 lbs RQ
Methanol	67-56-1	100 lbs RQ (F003)
Methanol	67-56-1	5000 lbs RQ
Methanol	67-56-1	100 lbs RQ (F003)

Pennsylvania Right To Know

The following chemicals are listed because of the additional requirements of Pennsylvania law:

Components	CASRN
Sodium aluminum silicate	1344-00-9
Water	7732-18-5
Polydimethylsiloxane hydroxy-terminated	70131-67-8
Triethoxy(octyl)silane	2943-75-1
Vinyl alcohol polymer with vinyl acetate	25213-24-5

California Prop. 65

WARNING: This product can expose you to chemicals including Methanol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

United States TSCA Inventory (TSCA)

All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

16. OTHER INFORMATION

Hazard Rating System

NFPA

Health	Flammability	Instability
2	1	0

HMIS

Health	Flammability	Physical Hazard
2/	1	0

Revision

Identification Number: 4074644 / A001 / Issue Date: 10/01/2019 / Version: 5.0

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

Legend

ACGIH	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	ACGIH - Biological Exposure Indices (BEI)
CAL PEL	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
OSHA P0	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
OSHA Z-1	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
PEL	Permissible exposure limit
STEL	Short-term exposure limit
TWA	8-hour, time-weighted average

Full text of other abbreviations

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Information Source and References

This SDS is prepared from information supplied by raw material suppliers.

WALTOOLS urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and

understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.

US