



FORM SHIELD FORM RELEASE

**Earth
Friendly**

Water base concrete form release

Form Release from Walttools is a uniquely formulated, water-based, Earth Friendly professional grade form release agent that dries to an invisible, waxy like film that allows the concrete to release with fewer imperfections. Form Release allows for a bondable concrete surface to the finished concrete. Form Release is V.O.C. compliant. It works to ensure clean, positive release on plywood, fiberglass, aluminum, steel, urethane and other concrete forming materials and form liners thereby extending the normal usable life of such forms.

INSTRUCTIONS

APPLICATION: Form Release can be applied in a number of methods such as by brush, roller, sprayer though for efficiency it is commonly sprayed applied using an atomizing or misting spray tip so that application may be in thin uniform films to maximize product performance and economy. Over application can cause puddling which should be avoided. Excess material or puddles should be removed with sponge, absorbent rag or squeegee. When properly applied, Form Release will not leave any residue or stain on the concrete, producing a smooth concrete surface ready for subsequent coatings. Care should be taken to NOT get form release onto reinforcing materials with the concrete to be poured

CLEAN-UP AND REMOVAL

Sprayers and applicators should be thoroughly cleaned with soap and water. Skin can be washed with soap and water.

PRECAUTIONS AND LIMITATIONS

- Use with adequate ventilation
- Wear protective clothing, gloves and eye protection (Goggles, Safety Glasses and/or Face Shield)
- Keep out of the reach of children
- Do not take internally
- In case of ingestion, seek medical help immediately
- May cause skin irritation upon contact, especially prolonged or repeated. If skin contact occurs, wash immediately with soap and water and seek medical help as needed.
- If eye contact occurs, flush immediately with clean water and seek medical help as needed
- Dispose of waste material in accordance with federal, state and local requirements
- Do not freeze

COVERAGE

Application Surface	General coverage
Smooth hard surfaces	1000-1500sq ft/gl
Medium density	750-1000 sq ft/gl
Dimensional lumber	500-750 sq ft/gl

*Coverage rates vary depending upon surface porosity and texture, and application thickness.
All new forms should be treated with two initial coats prior to use.

INSTRUCTIONS

APPLICATION: Form Release can be applied in a number of methods such as by brush, roller, sprayer though for efficiency it is commonly sprayed applied using an atomizing or misting spray tip so that application may be in thin uniform films to maximize product performance and economy. Over application can cause puddling which should be avoided. Excess material or puddles should be removed with sponge, absorbent rag or squeegee. When properly applied, Form Release will not leave any residue or stain on the concrete, producing a smooth concrete surface ready for subsequent coatings. Care should be taken to NOT get form release onto reinforcing materials with the concrete to be poured

CLEAN-UP AND REMOVAL

Sprayers and applicators should be thoroughly cleaned with soap and water. Skin can be washed with soap and water.

PRECAUTIONS AND LIMITATIONS

- Use with adequate ventilation
- Wear protective clothing, gloves and eye protection (Goggles, Safety Glasses and/or Face Shield)
- Keep out of the reach of children
- Do not take internally
- In case of ingestion, seek medical help immediately
- May cause skin irritation upon contact, especially prolonged or repeated. If skin contact occurs, wash immediately with soap and water and seek medical help as needed.
- If eye contact occurs, flush immediately with clean water and seek medical help as needed
- Dispose of waste material in accordance with federal, state and local requirements
- Do not freeze
- Refer to instructions and guidelines of any subsequent coating that will go onto released concrete

When using this product, the substrate preparation, application, performance and all other liabilities are strictly the end users responsibility. Walttools and it's affiliates offers no guaranty, warranty or other claims to the success or results from the use of this product. Walttools warrants the product to be free of defects and will replace or refund the purchase price of the product in the case that said products are proven defective. Any consequential damages including any labor costs are not covered by this warranty and are therefore not recoverable from the manufacturer or associated reseller.

NOTES

Please consult Material Safety Data Sheet (MSDS) and read Warranty information prior to use. This information can be requested by contacting customer service at 815.941.4215.

**T
R
U**

Walttools

IMPRESSIONS

Walttools, 1262 Leah Rd, Morris, IL 60450

888.263.5895

www.walttools.com